

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 10854-2 (1984): Cutter Suction Dredge Components, Part 2: Suction Pipe [TED 18: Inland, Harbour Crafts and Fishing Vessels]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

SPECIFICATION FOR CUTTER SUCTION DREDGE COMPONENTS

PART 2 SUCTION PIPE

1. Scope — Specifies the requirements of the suction pipe as a component in the cutter suction dredgers.

2. Requirements

2.1 Design — The diameter of the suction pipe shall be derived taking into consideration the following:

- i) Pump's output, and
- ii) The minimum velocity allowable in the pipe.

2.1.1 The suction mouth opening shall fit into the cutter below its center. This shall normally be of elliptical shape. The suction mouth area shall be chosen depending upon dredge material. The average area of the suction mouth shall usually be 1.25 times of the area of the suction pipe.

2.2 Material — The connected sections of the pipe shall be of mild steel conforming to IS : 226-1975 Structural steel (standard quality)'.

2.3 Construction — The suction pipe shall be assembled in flange-connected sections of 3 to 6 m long. The thickness of the pipe shall be not less than 14 mm.

EXPLANATORY NOTE

Suction pipe transports material from the cutter to the pump. It is supported beneath the ladder and is flexibly connected to the hull by a ball joint, trunnion elbow or rubber sleeve.

Adopted 31 March 1984

© June 1984, ISI

Gr 1